

Contents lists available at ScienceDirect

# Science of the Total Environment

journal homepage: www.elsevier.com/locate/scitotenv



Review

# Negative emissions technologies: A complementary solution for climate change mitigation




J.C.M. Pires

LEPABE - Laboratório de Engenharia de Processos, Ambiente, Biotecnologia e Energia, Faculdade de Engenharia da Universidade do Porto, Rua Dr. Roberto Frias, s/n, 4200-465 Porto, Portugal

#### HIGHLIGHTS

- NETs may be required as a complementary solution for climate change mitigation.
- Environmental impacts of a higher scale NETs deployment are crucial.
- Process integration may be performed to reduce the overall cost.
- Power to gas process and microalgal culture should be explored.

## GRAPHICAL ABSTRACT



## ARTICLE INFO

Article history:
Received 31 January 2019
Received in revised form 29 March 2019
Accepted 1 April 2019
Available online 2 April 2019

Editor: Huu Hao Ngo

Keywords:
Atmospheric CO<sub>2</sub> concentration
Biochar
Bioenergy with carbon capture and storage
Negative emission technologies
Sustainability

## ABSTRACT

Carbon dioxide  $(CO_2)$  is the main greenhouse gas (GHG) and its atmospheric concentration is currently 50% higher than pre-industrial levels. The continuous GHGs emissions may lead to severe and irreversible consequences in the climate system. The reduction of GHG emissions may be not enough to mitigate climate change. Consequently, besides carbon capture from large emission sources, atmospheric  $CO_2$  capture may be also required. To meet the target defined for climate change mitigation, the removal of  $10~{\rm Gt\cdot yr^{-1}}$  of  $CO_2$  globally by mid-century and  $20~{\rm Gt\cdot yr^{-1}}$  of  $CO_2$  globally by the end of century. The technologies applied with this aim are known as negative emission technologies (NETs), as they lead to achieve a negative balance of carbon in atmosphere. This paper aims to present the recent research works regarding NETs, focusing the research findings achieved by academic groups and projects. Besides several advantages, NETs present high operational cost and its scale-up should be tested to know the real effect on climate change mitigation. With current knowledge, no single process should be seen as a solution. Research efforts should be performed to evaluate and reduce NETs costs and environmental impact.

© 2019 Published by Elsevier B.V.

## Contents

1.	Introduction	50
2	Methodology	504

E-mail address: jcpires@fe.up.pt.


3. Direct air capture	504
3.1. Absorption	504
3.2. Adsorption	509
3.3. Ocean alkalinity enhancement	500
3.4. Soil mineralization	50
4. Indirect air capture	50
4.1. Afforestation	508
4.2. Ocean fertilization	509
4.3. Algae (seaweed and microalgae) culture	510
4.4. Bioenergy with carbon capture and storage	510
4.5. Biochar	51
5. Main research projects	51
6. Current and future economic and technical challenges	51
7. Conclusions	
Acknowledgements	512
References	512


#### 1. Introduction

Since the Industrial Revolution, anthropogenic activities have become the main driver of the global environmental change, shifting the Earth system to an unstable state (Steffen et al., 2007). Rockstrom et al. (2009) identified and quantified planetary boundaries that should not be surpassed to avoid unacceptable environmental changes. Three of nine identified boundaries have been already transgressed due to human action: (i) biodiversity loss; (ii) nitrogen cycle; and (iii) climate change. The latter has taken a high relevance due to the rapid environmental changes: (i) increase of temperature in atmosphere; (ii) decrease of the snow and ice covered regions; and (iii) rise of sea level (Change IPoC, 2013; Dawson et al., 2011; Meinshausen et al., 2009; Whiteley, 2011). These phenomena are related with greenhouse gas (GHG) emissions to atmosphere (and their accumulation), mainly carbon dioxide (CO<sub>2</sub>). Its atmospheric concentration has increased by 50% since the Industrial Revolution (270-275 ppm in 1750; 310 ppm in 1950; 408 ppm in 2018) (Allen et al., 2009; NOAA, 2018; Steffen et al., 2007). Consequently, the ocean has absorbed about 30% of the anthropogenic CO<sub>2</sub> emissions, causing its acidification and the associated consequences (e.g. adverse effects on biodiversity) (Doney et al., 2009; Hoegh-Guldberg et al., 2007; Orr et al., 2005). Global CO<sub>2</sub> emissions are about 36  $Gt_{CO2} \cdot yr^{-1}$  (fossil fuels emissions represent 91% of the CO<sub>2</sub> emitted by anthropogenic activities - https://www.co2.earth/ global-co2-emissions), which is higher than the uptake value by natural sinks (Le Quere et al., 2018). A positive balance of about 15 Gt<sub>CO2</sub>·yr<sup>-1</sup> (equivalent to 4.1  $Gt_C \cdot yr^{-1}$ ) is associated to an increase of atmospheric  $CO_2$  concentration of about 2 ppm·yr<sup>-1</sup> (Goeppert et al., 2012; Lackner, 2009). Fig. 1 shows the tendency of the atmospheric CO<sub>2</sub> concentration (NOAA, 2018), showing an annual oscillation (in Northern hemisphere, atmospheric CO2 levels decrease about 5 ppm during summer and increase about 7 ppm in winter). The atmospheric CO<sub>2</sub> concentration presents the same temporal behaviour of the global mean temperature (see Fig. 2), showing that these phenomena are correlated.

Aiming to reduce the atmospheric  $CO_2$  concentration, many countries decided to reduce the carbon intensity of their economies (Dovi et al., 2009; Meinshausen et al., 2009; Moss et al., 2010; Pires et al., 2011). In the  $21^{st}$  Conference of the Parties (COP21) that occurred in Paris (2015), an agreement was achieved to reduce GHG emissions in order to avoid the increase of global temperature of 2 °C. One of the main commitments was the protection of the forest, maintaining or even increasing this natural sink. One of the short-term solutions to reduce  $CO_2$  emissions is the carbon capture and storage (CCS). This procedure is mainly applied to capture  $CO_2$  from flue gases (4–14%) and the achieved  $CO_2$  enriched stream is then transported to geological reservoirs to be stored. However, about 50% of the  $CO_2$  emissions are from diffuse sources, e.g. aircraft, shipping or automobiles. Moreover, the

application of the climate change mitigation actions has been delayed due to the economic interests (high dependence of fossil fuels to get energy). Therefore, taking into account the long residence time in the atmosphere, atmospheric  $CO_2$  capture may also be required (also





**Fig. 1.** Global average of monthly mean concentration (in ppm) of atmospheric carbon dioxide for different periods at Mauna Loa Observatory, Hawaii (NOAA, 2018); smooth lines are achieved after correction for the average seasonal cycle.




Fig. 2. Air surface temperature anomaly (AST) time series from Goddard Institute for Space Studies (GISS, 2018); smooth lines are achieved after correction for the average seasonal cycle.

known as negative emission technologies - NETs) (Azar et al., 2013; Jones, 2011; Keith, 2009; Lackner and Brennan, 2009; McLaren, 2012; Pielke, 2009). Despite their process drawbacks (CO<sub>2</sub> separation is more difficult, thus involving a higher operational cost), NETs present a set of interesting advantages (Archer et al., 2009; Shepherd et al., 2009): (i) CO<sub>2</sub> capture from any economic activity emitted at different locations and time; (ii) location of the capture unit near the storage site (avoiding the transport costs and its infrastructure); and (iii) the applied separation process is not influenced by other pollutants also emitted by emission point sources (e.g. nitrogen and sulphur oxides), due to their lower atmospheric concentration (Azar et al., 2006; Goeppert et al., 2012; Lackner, 2009; Lackner et al., 2012; Read and Lermit, 2005). Table 1 presents recent research studies with simulated scenarios that showed the need for NETs. However, NETs should be not seen as the solution for the delay of the application of the climate change mitigation policies, but as the complementary solution to the ones defined in COP21. Besides the cost of negative emissions, NETs were not tested at the scale that is modelled in climate scenarios and may not have the required impact on atmospheric CO<sub>2</sub> mitigation (Jones, 2011; Larkin et al., 2018).

The capture of  $CO_2$  from air does not need to extract all the  $CO_2$ , but it should collect it as efficiently as possible (typically the economic removal efficiency is less than 50%). This capture cannot be too much expensive, being a reasonable price \$30 per ton of CO<sub>2</sub> (Lackner, 2009; Lackner et al., 2012). NETs can be divided in: (i) direct air capture, if physicochemical processes are applied (absorption, adsorption, ocean alkalinity enhancement, and soil mineralization); and (ii) indirect air capture, if biological processes are used (afforestation, ocean fertilization, algal culture, bioenergy with carbon capture and storage - BECCS, and biochar) (McLaren, 2012; Workman et al., 2011). Fig. 3 shows the most important carbon fluxes between atmospheric, land, ocean and geological reservoirs regarding the presented NETs. Table 2 shows some published reviews about different NETs and their focus. This paper aims to present a comprehensive overview of the recent technological advances of the main NETs, presenting also their advantages and drawbacks. Results of main research projects and the economic and technical challenges now and into the future are discussed.

## 2. Methodology

This study was performed by searching peer-reviewed research papers (until August 2018) using Scopus, Web of Science, ScienceDirect, Wiley and Springer databases by combining the following keywords (and its possible variations): "Zero Carbon Emissions", "Negative Emission Technologies", "BECCS", "Air Capture", "Direct Air Capture", "Indirect Air Capture" and "Biochar". The acknowledgements of those papers were also analysed to search the active research projects in this topic. Then, the information in web sites and reports of these projects were also considered.

# 3. Direct air capture

The concept of capturing  $CO_2$  from ambient air is not new. This process was already applied in scrubbers for closed environments (e.g. submarines and spacecraft) to reduce the  $CO_2$  concentration to values below 5000 ppm (Lu et al., 2013). As a climate mitigation option, Lackner was the first one to propose in 1999. However, atmospheric  $CO_2$  capture requires high energetic demand, mainly to promote the movement of high amount of air through the scrubber, although wind can be used as air transport. As it is not economically viable to apply a significant amount of energy (heat and work), many separation processes that are applied to  $CO_2$  capture from high concentrated streams (flue gases) cannot be considered in air capture. Below, direct air capture methodologies applied for atmospheric  $CO_2$  are presented: (i) absorption; (ii) adsorption; (iii) ocean alkalinity enhancement; and (iv) soil mineralization. Table 3 presents some relevant issues in research studies regarding direct  $CO_2$  capture.

## 3.1. Absorption

Absorption is a physicochemical process in which compounds are dissolved in a liquid phase (Pires et al., 2011). The main difference from adsorption is that these compounds are retained in the liquid volume, not on the solid sorbent surface (adsorption). CO<sub>2</sub> absorbents are monoethanolamine (MEA) and strong bases, such as calcium hydroxide (Ca(OH)<sub>2</sub>), sodium hydroxide (NaOH), and potassium hydroxide

**Table 1**Recent scenario modelling studies.

NET	Relevant issues	Reference
BECCS	Evaluation of the role of power generation from bio plants with CCS to achieve a low climate target by 2100 using the optimization model TIAMFR (TIMES Integrated Assessment Model France). Global and regional analyses to quantify BECCS potential in industrialized, fast-developing and developing countries. High dependence of BECCS as a negative emissions process technology on the future development of CCS technology.	Selosse and Ricci (2014)
BECCS	Assessment of economic and deployment implications for BECCS in the electricity system of western North America under aggressive time frames and carbon emissions limitations (SWITCH optimization model).	Sanchez et al. (2015)
All	Quantification of the conventional mitigation and negative emissions required for RCP2.6 (IPCC scenario likely to limit the global warming below 2 °C) based state-of-the-art carbon-climate models. In the best-case, negative emissions of 0.5–3 Gt <sub>C</sub> ·yr <sup>-1</sup> and storage capacity of 50–250 Gt <sub>C</sub> are required; In the worst case, those requirements are 7–11 Gt <sub>C</sub> ·yr <sup>-1</sup> and 1000–1600 Gt <sub>C</sub> , respectively.	Gasser et al. (2015)
BECCS	Modelling of a zero emissions scenario based on the A1T scenario of IPCC-SRES. Results suggested that zero emissions scenario may be possible in this century. Energy supply structure (with BECCS) under the zero emissions scenarios was described.	Tokimatsu et al. (2016)
All	Impact assessment on the global carbon cycle across different time horizons, considering different balances of emissions and fluxes, and the responses of the natural carbon cycle. CMIP5 model simulations to quantify how the Earth system may respond to NETs.	Jones et al. (2016)
All	Projection of energy and land-use emissions mitigation pathways through 2100.  Anthropogenic emissions need to peak within the next 10 years, to maintain realistic pathways to meeting the COP21 emissions and warming targets.  Fossil fuel consumption will probably need to be reduced below a quarter of primary energy supply by 2100.	Walsh et al. (2017)
BECCS	Development strategy of low carbon scenarios that consider interaction of economically viable bioenergy and/or BECCS technological flow, biophysical limit of bioenergy productivity and food security.  Evaluation of several bioenergy feedstock and conversion technologies with and without CCS with GRAPE (Global Relationship Assessment to Protect the Environment).	Kato et al. (2017)
Afforestation BECCS	Evaluation of alternative options to greatly reduce the volume of CO <sub>2</sub> removal (CDR) from atmosphere to achieve the 1.5 °C goal. Almost all scenarios still rely on BECCS and/or reforestation. Investment in the development of CDR options remains an important strategy if the international community intends to implement the Paris target.	van Vuuren et al. (2018)

BECCS – bioenergy with carbon capture and storage; IPCC - Intergovernmental Panel on Climate Change; NET – negative emissions technology.

(KOH). MEA is the most used sorbent in  $CO_2$  capture in flue gases. However, the corrosion is its main problem (Goeppert et al., 2011). Thus, these amines are generally used in 20–30% concentration in water. These procedure increases the energetic demand in regeneration step (stripping) due to the high heat capacity of these aqueous solutions. Moreover, these sorbents present lower stability in the presence of air. Air moisture is one the most important problem in absorption process

for atmospheric  $CO_2$  capture. Inagaki et al. (2017) evaluated the modification of alkylamines with hydrophobic phenyl group to increase their selectivity between  $CO_2$  and water. Additionally, the tested xylylenediamines were able to capture  $CO_2$  without hydration, reducing the energy requirements for recovery of the absorbent.

CO<sub>2</sub> capture can be also performed by wet scrubbing systems based on cycling technologies using strong bases (Baciocchi et al., 2006; Keith et al., 2006; Zeman, 2007). CO<sub>2</sub> is then recovered by calcination, pressurized and stored. The most studied sorbents are sodium and calcium hydroxide. NaOH solution presents some advantages over Ca(OH)<sub>2</sub> (Stolaroff, 2006): (i) lower vapour pressure, reducing water loss; (ii) high hydroxide concentrations enhancing CO<sub>2</sub> capture kinetics; and (iii) reduced probability of accumulation of solid carbonates. NaOH spray-based contactor was studied for air capture, aiming to estimate the costs of a capture unit with this system (Stolaroff et al., 2008). In this process, water loss is significant (20 mol H<sub>2</sub>O per mol of CO<sub>2</sub> at 15 °C and 65% relative humidity), which can be lowered by optimizing the system design and operating conditions. The determined cost for the full-scale system is  $96\$ \cdot t_{CO2}^{-1}$  in the base case, which can vary between 53 and 127\$\cdot t\_{CO2}^{-1}\$ depending of the operating parameters and the assumptions concerning capital cost and mass transfer kinetics. The total energy requirement was from 190 to 390 kJ·mol<sup>-1</sup> for the tested conditions.

Keith et al. (2006) developed the lime/soda process for CO<sub>2</sub> capture (see Fig. 4). Firstly, atmospheric CO<sub>2</sub> is absorbed in NaOH solution forming sodium carbonate (Na<sub>2</sub>CO<sub>3</sub>) in a scrubbing tower. Then, Na<sub>2</sub>CO<sub>3</sub> solution reacts with Ca(OH)<sub>2</sub>, generating NaOH (returning to scrubbing tower) and calcium carbonate (CaCO<sub>3</sub>), which precipitates. This regeneration process (Kraft chemical recovery process) is already applied in pulp and paper mills and other industries. After filtering, CaCO<sub>3</sub> is converted to lime by calcination reaction. To increase the purity of CO<sub>2</sub> gaseous stream, this reaction can be performed in a CO<sub>2</sub> environment. The estimated cost was  $500\$ \cdot t_C^{-1}$  (140 $\$ \cdot t_{CO2}^{-1}$ ). Process intensification should be perform to decrease the overall cost to 40-80  $t_{CO2}^{-1}$ . One of the drawbacks of this process is the significant water loss due to the high amount of air pumped to scrubbing tower. Moreover, the process presents a significant energy (mainly for pumping) requirements: between 30 and 88 kJ·mol<sup>-1</sup> (Zeman, 2007). To reduce costs, the scrubbing tower should be designed with large cross-section area to decrease the height of the liquid absorber level (reducing the pressure drop of gaseous stream in the scrubbing tower). Baciocchi et al. (2006) also studied lime/soda process for CO<sub>2</sub> capture. The authors assessed two process designs and total net heat requirements for two different process configurations, achieving the values of 5.3 and 2.6 GJ· $t_{CO2}^{-1}$ . Zeman (2007) also performed energy and material balances of this process for CO<sub>2</sub> capture from atmosphere. The energy consumption was calculated as 350 kJ·mol<sup>-1</sup> of captured CO<sub>2</sub> (mainly thermal energy for calcination and mechanical power for air movement), lower than the values achieved by other authors (Baciocchi et al., 2006; Keith et al., 2006).

# 3.2. Adsorption

In absorption processes, the thermal energy demand in regeneration step is the main disadvantage. Thus, CO<sub>2</sub> capture in solid adsorbents (physical adsorption) was also studied as an alternative (Belmabkhout et al., 2010; Goeppert et al., 2011; Jones, 2011; Lu et al., 2013). Zeolites, activated carbon and alumina have low CO<sub>2</sub> adsorption capacities, being not considered in air capture. Amines immobilized in solid supports are characterized by lower regeneration temperatures, being also considered a potential solution for atmospheric CO<sub>2</sub> capture (Goeppert et al., 2011; Wurzbacher et al., 2011). These materials have other interesting characteristics, such as a high specific surface area, high CO<sub>2</sub> selectivity at diluted concentrations and tolerance to moisture. The tolerance to moisture is an important characteristic when compared with zeolites in which CO<sub>2</sub> selectivity decreases in the presence of water. Table 4




Fig. 3. The main flows of carbon (gray arrows denote carbon removal through NETs) among atmospheric (A), land (L), ocean (O) and geological reservoirs (G): (a) direct air capture (through absorption and adsorption); (b) ocean alkalinity enhancement and ocean fertilization; (c) soil mineralization, afforestation and biochar (addition to soil); and (d) bioenergy with carbon capture and storage (Smith et al., 2016).

shows the main results of different adsorbents when applied for atmospheric  $CO_2$  capture.

Goeppert et al. (2011) evaluated the atmospheric  $CO_2$  capture through a polyamine based solid adsorbent. The moisture effect on the adsorption capacity was studied at room temperature and the regeneration of the adsorbent after adsorption/desorption cycles. The determined adsorption capacity was 1.74 mmol·g<sup>-1</sup>, which was greater than the reported value for the hyperbranched aminosilica adsorbent (1.44 mmol·g<sup>-1</sup>). This study showed that adsorbent based on supported amines are promising low cost materials for  $CO_2$  capture from air

An emerging material for  $\mathrm{CO}_2$  capture is metal-organic frameworks (MOFs), which are crystalline materials consisting of coordination bonds between transition metal cations (e.g.,  $\mathrm{Al}^{3+}$ ,  $\mathrm{Cr}^{3+}$ ,  $\mathrm{Cu}^{2+}$ , or  $\mathrm{Zn}^{2+}$ ) and multidentate organic linkers (e.g., carboxylate, pyridyl) in a three-dimensional network with uniform pore diameter often in the range 3 to 20 Å (Mazzotti et al., 2013). These materials can also be used for gas storage, catalysis and sensing applications. Shekhah et al. (2014) tested MOFs with pore of 3.5 Å for low concentration  $\mathrm{CO}_2$  capture. MOF structure was characterized by optimal  $\mathrm{CO}_2$  energetics (allow reversible physical adsorption-desorption) and a pore size suitable for direct air capture. In the tested  $\mathrm{CO}_2/\mathrm{N}_2$  gas mixture,  $\mathrm{CO}_2$  apparent selectivity at 1000 ppm  $\mathrm{CO}_2$  was not affected by the presence of humidity through the analysis of breakthrough tests.

Besides geological storage, the captured  $CO_2$  can be applied in chemical synthesis processes, e.g. power to gas conversion (Schiebahn et al., 2015; Veselovskaya et al., 2017). With the increase of renewable energy (wind and solar) integration in the electrical grid, the variability of power supply increased and is difficult to predict; thus, this fact puts in risk the electrical grid stability. Consequently, there is an increasing need to find a technology that allows the storage of the excess of electricity produced by fluctuating energy sources. Veselovskaya et al. (2017) evaluated the  $CO_2$  capture from air using a sorbent based on composite material  $K_2CO_3/Al_2O_3$  in temperature swing adsorption (TSA) cycles. The combination between air capture and methane production through Sabatier process (commercial nickel catalyst NKM-2V) was implemented with a two reactor system, presenting high experimental conversions of desorbed  $CO_2$  to methane.

# 3.3. Ocean alkalinity enhancement

The planet has natural carbon sinks (regions where  $\mathrm{CO}_2$  is removed from atmosphere) and sources (carbon is released back to atmosphere) – see carbon flows in Fig. 3 with black colour. Ocean represents the main carbon sink, removing about one third of the anthropogenic emissions from the atmosphere.  $\mathrm{CO}_2$  is absorbed in water and reacts with ocean minerals, which help to neutralize ocean acidification. However, the increase of  $\mathrm{CO}_2$  emissions creates an unbalance on this system, as oceans

**Table 2**Review papers about NETs.

NET	Aims	Reference
Absorption/adsorption	Recent advances in solvents, adsorbents, and membranes for post-combustion $CO_2$ capture. Review of the concept of extracting $CO_2$ directly from ambient air as a means of reducing the global atmospheric $CO_2$ concentration and comparison with post-combustion process.	Jones (2011)
Algal culture	Holistic detailed overview of the process of carbon sequestration, focusing biological carbon mitigation.  Assessment of the commercial applications of microalgal biomass from microalgae.  Technical barriers (environmental concerns) and economic matters to be overcome.	Farrelly et al. (2013)
BECCS	Overview of BECCS at the systems level, based on relevant information from the recent 5th Assessment Report (AR5) of IPCC. Role assessment of BECCS in stabilising atmospheric CO <sub>2</sub> concentrations. Not address or discuss specific BECCS capture technologies, their technical optimization and RD&D requirements.	Kemper (2015)
Adsorption	Systematic analysis focusing the key technical parameters required for CO <sub>2</sub> capture using physical adsorbents. Recently developed class of MOF adsorbents represent a breakthrough finding for CO <sub>2</sub> capture in diluted streams using physical adsorption.	Belmabkhout et al. (2016)
Absorption/adsorption	Historical overview of the field of direct air capture with extensive description of the chemical sorbents application.  New materials need to be further investigated and developed with a practical sorbent—air contacting process.	Sanz-Perez et al. (2016)
Biochar	Assessment of the effect size of biochar amendment on soil CO2 fluxes, SOC, and MBC contents. Key factors influencing the response of soil $CO_2$ fluxes, SOC, and MBC to biochar amendment.	Liu et al. (2016)
Soil mineralization	Review of the potential of enhanced weathering (EW), applying crushed reactive silicate rocks (such as basalt) on tropical agricultural and tree plantations to offset fossil fuel CO <sub>2</sub> emissions. Identification of nine priority research areas in the topic.	Edwards et al. (2017)
All	Scientometric methods and topic modelling to identify and characterize the available evidence on NETs as recorded in the Web of Science.	Minx et al. (2017)
AII	Comprehensive and systematic assessment of the academic literature on NETs.  Potential role of NETs for reaching the international climate goals.  Costs, potentials, and side-effects for these technologies.  Innovation and scaling challenges required for NETs deployment.	Fuss et al. (2018); Minx et al. (2018); Nemet et al. (2018)

BECCS – Bioenergy with carbon capture and storage; IPCC - Intergovernmental Panel on Climate Change; MBC – microbioal biomass carbon; MOF – metal–organic frameworks; NET – negative emissions technology; SOC – soil organic carbon.

do not have such high capacity to absorb (and neutralize) all emitted CO<sub>2</sub>, leading to the change in pH levels in ocean surface water.

The addition of alkaline nature compounds (e.g., CaOH,  $Ca(HCO_3)_2$ ) to ocean surface water can enhance the removal of CO2 from atmosphere and increase of total ocean CO<sub>2</sub> storage (Rau, 2011; Rau and Caldeira, 1999; Renforth and Kruger, 2013). This procedure may have a strong impact on the chemistry of the surface waters (with unknown consequences to the marine environment), requiring detailed studies before its implementation. Moreover, there are also concerns about the impact of massive land-based mineral extraction, processing and transportation (Rau, 2014). Renforth et al. (2013) presented the engineering challenges of the ocean liming. Through a techno-economic analysis, the authors determined that 1.4–1.7 t of limestone is required to remove 1 t of atmospheric CO<sub>2</sub>, being needed 0.6–5.6 GJ· $t_{CO2}^{-1}$  of thermal energy and 0.1–1.2 GJ· $t_{CO2}^{-1}$  of electrical energy. Analysing the costs of the process, ocean liming may require  $72-159\$ \cdot t_{CO2}^{-1}$ . Paquay and Zeebe (2013) applied carbon-cycle model LOSCAR to analyse the effect of ocean alkalinity enhancement in its pH and atmospheric CO2 concentration for the period between 2020 and 2040. Ten carbon emission scenarios were simulated. These authors also calculated the required amount of CaO and the correspondent cost to maintain the ocean pH above 8.

# 3.4. Soil mineralization

Soil contains over 2000 Gt<sub>C</sub> (the greatest land-based reservoir for carbon in the planet) and the covering vegetation captures up to 3 Gt<sub>C</sub>·yr<sup>-1</sup>, representing an important earth carbon sink (Farrelly et al., 2013). The  $CO_2$  exchange between soil and atmosphere is three times higher than the exchange between the ocean and atmosphere. Soils can sequester atmospheric  $CO_2$  by three ways (Lackner, 2002): (i) accumulation of organic carbon resulting from plant growth (representing a fragile stock as the degradation occurs at a rate depending on the storage environment); (ii) rock weathering (promoting the dissolution of inorganic carbon in soil solution); and (iii) precipitation of carbonate materials (stable carbon sink). The enhancement of  $CO_2$ 

uptake in the soil is a form of carbon abatement that is inexpensive, as it is a passive process (low energy input – similar to the construction of wetlands for treatment of polluted waters). The potential  $CO_2$  removal by enhanced weathering (addition of carbonate or silicate minerals to soils to increase carbonation process kinetics) was estimated to be about 1  $G_{C}$ ·yr $^{-1}$  in 2100 (Kohler et al., 2010). The observed climate change has a complex interaction with soil response regarding carbon mineralization kinetics (Keller et al., 2004; Krevor and Lackner, 2011; Qafoku, 2015). Besides the high atmospheric  $CO_2$  concentrations and temperature increase, intense rainfall increase the extent and rates of carbonation by removing the reaction products (by surface runoff or percolating water). Heat waves and droughts may also promote the  $CO_2$  removal, as these phenomena changes the physical properties of rocks and minerals.

## 4. Indirect air capture

Currently, the natural processes of atmospheric CO<sub>2</sub> capture are mainly based on biological processes. Nature converts CO<sub>2</sub> into organic carbon (carbohydrates, cellulose and lipids) by photosynthesis (producing also oxygen) in plants, trees and algae. For instance, photosynthesis process in the ocean captures about 40% of the atmospheric CO<sub>2</sub> (Goeppert et al., 2012; Pires et al., 2012; Watanabe and Kuwae, 2015). In addition, these processes were responsible for the stabilization of atmospheric CO<sub>2</sub> concentration (280 ppm) during a long time period before the industrial revolution (Pielke, 2009). The enhancement of these natural processes of CO<sub>2</sub> capture has an important advantage against the direct air capture methods, regarding energy requirements. While biological processes uses direct solar energy in CO<sub>2</sub> fixation, the physical and chemical processes requires heat or electrical energy (McLaren, 2012). Moreover, the CO<sub>2</sub> storage is costly and the long term sequestration is not guaranteed (Farrelly et al., 2013; Pires et al., 2011). However, photosynthesis presents lower efficiency in the conversion of solar into chemical energy (most crops present efficiencies between 0.5 and 2%), when compared to solar cells to produce electricity. In the next sections, the main indirect air capture processes are described: (i) afforestation;

**Table 3** Direct air capture studies.

NET	Relevant issues	Reference
Absorption	Test of hydrophobic phenyl group into alkylamines of CO <sub>2</sub> absorbents (improved selectivity between CO <sub>2</sub> and water).	Inagaki et al. (2017)
	Evaluation of a NaOH spray-based contactor for use in an air capture system by estimating the cost and energy requirements	Stolaroff et al. (2008)
	Experimental investigation into the combined sodium/calcium capture process.	Zeman (2008)
	Energy and Material Balance of soda/lime process for CO <sub>2</sub> capture.	Zeman (2007)
Adsorption	Characterization of adsorption kinetics of a novel moisture swing process for air capture. Transient heat and mass transfer model for the desorption step of a temperature–vacuum swing adsorption for air capture.	Wang et al. (2016) Wurzbacher et al. (2016)
Ocean alkalinity enhancement	Effect of ocean alkalinity on carbon sequestration.	Renforth and Henderson (2017)
	Assessment of ocean liming consequences and costs.	Paquay and Zeebe (2013)
Soil mineralization	Passive Sequestration of Atmospheric CO <sub>2</sub> through Coupled Plant-Mineral Reactions in Urban soils.	Manning and Renforth (2013)

(ii) ocean fertilization; (iii) algal culture; (iv) bioenergy with carbon capture and storage; and (v) biochar. Table 5 presents some relevant issues in research studies regarding indirect CO<sub>2</sub> capture.

# 4.1. Afforestation

Afforestation can be also considered a NET, as the forests can safely store several amounts of carbon sequestered by photosynthesis during a long period (Boucher et al., 2012; Obersteiner et al., 2010). From all the  $CO_2$  mitigation options, forest and soil management are the most ready techniques. The increase of forest area by planting new forests or better management of the current natural and plantation forests will improve the carbon sequestration (Shepherd et al., 2009). Biomass provides four routs for  $CO_2$  capture: (i)  $CO_2$  capture and storage in biological form (soil organic carbon and carbon accumulated in plants); (ii)

remote storage by biomass harvesting and application (not for combustion processes – e.g. furniture and construction materials); (iii) energy production, reducing the dependence on fossil fuels (biomass represents only 1% of the world generated power); and (iv) energy production with remote  $CO_2$  sequestration (BECCS – power production with post-combustion  $CO_2$  capture and geological storage).

The atmospheric carbon capture by afforestation and reforestation is stored in living biomass. However, the deforestation and the conversion of the land to agriculture practices affect the soil organic carbon stock, causing the release of 20 to 50% of the soil carbon to the atmosphere (Wei et al., 2014). Kindermann et al. (2008) estimated that 50% reduction in deforestation may avoid emissions of 1.5–2.7  $Gt_{CO2} \cdot yr^{-1}$  in the period from 2005 to 2030. Therefore, the success of atmospheric  $CO_2$  capture with this technique depends of long-term forest management (and forest fire mitigation).

Afforestation may have a strong impact in other earth systems. Regarding land use, the CO<sub>2</sub> removal of 1.1–3.3 Gt<sub>CO2</sub>·yr<sup>-1</sup> may require 320-970 million hectares of land (Smith et al., 2016). Moreover, high nutrient (nitrogen and phosphorus) requirements were also estimated in the same study. Besides carbon uptake, forestry influences the climate through albedo changes, emissions of volatile organic compounds and microbes (Ellison et al., 2017). Additionally, captured carbon is vulnerable to changes of political priorities, illegal logging (the main contribution to current rates of deforestation), fires, pests and diseases. The current trend of global temperature leads to drying soils and vegetation (water availability/requirements may be an important limit for forest protection), increasing the probability of occurrence of forest fires (recently in several European countries, USA and Australia). Besides destroying the ecosystems (and sometimes loss of human lives), forest fires are responsible for the emission of large quantity of CO<sub>2</sub> that was captured during a long period. Thus, the low security of carbon stored in living biomass requires policy measures to protect and expand the forest. One policy decision that could help in forest protection is the allocation of carbon credits to their preservation (Shepherd et al., 2009).

The afforestation may also enhance the soil organic carbon (SOC), which has an extended mean residence time: 50 to 80 years (Lorenz and Lal, 2014a; Lorenz and Lal, 2014b; Schmidt et al., 2019). Thus, it can have an important contribution on  $\rm CO_2$  capture from air. On the other hand, for agricultural soils, SOC is dependent on the applied agronomic practices (Lal et al., 2004; Marland et al., 2003). The capacity of




Fig. 4. Soda/lime process for CO<sub>2</sub> capture (Zeman, 2008).

**Table 4** Atmospheric CO<sub>2</sub> capture based on adsorption process.

Sorbent	Experimental setup	Sorption capacity	Energy consumption	Reference
Amine-based nanofibrillated cellulose	[CO $_2$ ] = 506 ppm; RH = 40%; $T_a$ = 25 °C; $T_d$ = 90 °C; ADP - 2 h/1 h.	SAC = 1.39 mmol <sub>CO2</sub> g <sup>-1</sup> ; DAC = 0.695 mmol <sub>CO2</sub> g <sup>-1</sup>	n/a	Gebald et al. (2011)
Amine-bearing mesoporous silica	$[CO_2] = 400 \text{ ppm}; RH = 27\%; T_a = 25 \text{ °C};$ ADP - n/a.	SAC = 0.98 mmol <sub>CO2</sub> g <sup>-1</sup> ; DAC = 2.04 mmol <sub>CO2</sub> g <sup>-1</sup>	n/a	Belmabkhout et al. (2010)
Hyperbranched aminosilica	$[CO_2] = 400 \text{ ppm}; T_a = 25 \text{ °C}; T_d = 110 \text{ °C}.$	$SAC = 1.72 \text{ mmol}_{CO2} \text{ g}^{-1}.$	n/a	Choi et al. (2011)
Metal—organic frameworks	$[CO_2] = 390 \text{ ppm}; T_a = 25 \text{ °C}; T_d = 150 \text{ °C};$ ADP - 1 h/0.5 h.	$SAC = 2.0 \text{ mmol}_{CO2} \text{ g}^{-1};$ $DAC = 1.05 \text{ mmol}_{CO2} \text{ g}^{-1}$	n/a	McDonald et al. (2012)
PPN-6-CH <sub>2</sub> DETA	$[CO_2] = 400 \text{ ppm}; T_a = 295 \text{ K};$	$SAC = 1.04 \text{ mmol}_{CO2} \text{ g}^{-1}.$	n/a	Lu et al. (2013)
FS-PEI-50	[CO2] = 420 ppm; Ta = 25 °C; Td = 85 °C; dry conditions; ADP – 7.1 h/3 h.	SAC = 1.71 mmol <sub>CO2</sub> g <sup>-1</sup> ; DAC = 1.65-1.71 mmol <sub>CO2</sub> g <sup>-1</sup>	n/a	Goeppert et al. (2011)
FS-PEI-33	$[CO_2] = 420 \text{ ppm}; T_a = 25 \text{ °C}; T_d = 85 \text{ °C}; RH = 67\%.$	$SAC = 1.74 \text{ mmol}_{CO2} \text{ g}^{-1}.$	n/a	Goeppert et al. (2011)
FS-PEI	$[CO_2] = 400 \text{ ppm}; T_a = 25-35 \text{ °C}; T_d = 70-100 \text{ °C}; P_d = 65 \text{ mtorr}.$	$SAC = 2.4 \text{ mmol}_{CO2} \text{ g}^{-1}$	82 kJ mol <sub>CO2</sub>	Goeppert et al. (2014)
Diamine-functionalized silica gel	[CO <sub>2</sub> ] = 400-440 ppm; $T_a$ = 25 °C; $T_d$ = 90 °C; $P_d$ = 30 mbar; RH = 0-80%; ADP (TVSA) - 3 h/1.25 h.	$DAC = 0.27 \text{ mmol}_{CO2} \text{ g}^{-1}$	9.6 kJ mol <sup>-1</sup> <sub>CO2</sub> (work); 430 kJ mol <sup>-1</sup> <sub>CO2</sub> (thermal).	Wurzbacher et al. (2011)
N-(2-aminoethyl)-3-aminopropylmethyldimethoxysilane modified nanofibrillated cellulose	[CO $_2$ ] = 400–530 ppm; T $_a$ = 30 °C; T $_d$ = 90 °C; P $_d$ = 30 mbar; RH = 60%; ADP (TVSA) – 2.5 h/0.75 h.	$DAC = 0.90 \text{ mmol}_{CO2} \text{ g}^{-1}$	n/a	Gebald et al. (2013)
Hydrolytically stable fluorinated metal-organic framework	$[CO_2]$ = 400 ppm; $T_a$ = 25 °C; $T_d$ = 55 °C; $P_d$ = vacuum 30 mbar.	$SAC = 1.3 \text{ mmol}_{CO2} \text{ g}^{-1}$	54 kJ mol <sub>CO2</sub>	Bhatt et al. (2016)

ADP – adsorption/desorption cyclic period; CC – cyclic capacity; DAC – dynamic adsorption capacity; FS-PEI - Fumed silica impregnated with polyethylenimine; RH – relative humidity; SAC = static adsorption capacity; T – temperature; TVSA - temperature-vacuum swing adsorption.

soils to accumulate organic carbon is limited and uncertain due to climate change effects. SOC management also involves management of the main macronutrients (nitrogen and phosphorus). SOC stocks may be increased by: (i) enhancing plant residues and root inputs to soils; (ii) adding organic matter, such as manure and compost (residue management); (iii) reducing decomposition losses, and (iv) promoting the crop rotation.

## 4.2. Ocean fertilization

Ocean fertilization aims to increase the biomass productivity by adding macronutrients (e.g. nitrogen and phosphorus) and micronutrients (e.g. iron) (Lampitt et al., 2008; Shepherd et al., 2009; Singh and Ahluwalia, 2013). The expected biological matter can then

**Table 5** Indirect air capture studies.

NET	Relevant issues	Reference
Afforestation	Cost estimation of reducing carbon emissions through avoided deforestation.	Kindermann et al. (2008)
Ocean	Comprehensive assessment of the global	Harrison
fertilization	potential for carbon sequestration from ocean fertilization.	(2017)
Algal culture	Demonstration and evaluation the concept of atmospheric CO <sub>2</sub> capture for enhanced algae cultivation.	Brilman et al. (2013)
	Life cycle assessment and economic analysis of ocean afforestation.	N'Yeurt et al. (2012)
BECCS	Evaluation of a 360 h in situ calcium looping	Diego and
	experiment in La Robla 300 kWh facility in continuous mode.	Alonso (2016)
	Potential of municipal solid waste as a resource for BECCS.	Pour et al. (2018)
Biochar	Potential assessment for negative emissions from soil carbon sequestration and biochar addition to land; impact assessment on land use, water, nutrients, albedo, energy and cost.	Smith (2016)
	Effect of feedstock, highest heating temperature	Crombie and
	(HTT), residence time at HTT and carrier gas flow	Masek (2015)
	rate on the distribution of pyrolysis co-products and their energy content	
	and then energy content	

sink and be stored in deep ocean. The required nutrients and their quantity (to promote the algal growth) depend on the relative amounts of the available nutrients in ocean. Redfield ratio (C:N:P:Fe – 106:16:1:0.001) is considered the optimal nutrient proportion for algal growth.

Two field experiments were performed with addition of phosphorus in low nutrient waters (Krom et al., 2005): (i) using concentrated phosphoric acid mixed with sodium bicarbonate; and (ii) using anhydrous monosodium phosphate. In the Mediterranean, the addition of phosphorus was associated with the growth of bacteria and zooplankton, and a modest increase of nitrogen fixation rates. Contrary to what was expected, phytoplankton biomass and chlorophyll presented a slight decrease. Similar effects were also observed with the field experiment in northwest Africa. Concerning nitrogen, no experiments were performed by adding this nutrient in a biologically available form. Iron addition to ocean is the most studied fertilization technique (started in 1988). Several research studies were performed in different regions (Aumont and Bopp, 2006; Boyd et al., 2007; Cao and Caldeira, 2010). Main results of these field experiments were (Williamson et al., 2012): (i) increase of pigment chlorophyll-a levels by 2-25 times, associated with increase of carbon fixation; (ii) nutrient uptake rates changed and photosynthetic efficiency increased; (iii) the response to iron addition was more effective in warmer waters; (iv) the dominant phytoplankton changed; and (v) bacterial and biomass production increased 2–15 times.

There are some side effects of the ocean fertilization (Lampitt et al., 2008). First, the excess of nutrients may lead to eutrophication (coastal phenomenon of worldwide concern) in which main consequences are the development of harmful algal blooms and the reduction of oxygen levels, affecting aquatic ecosystem. Second, despite the reduction of the current trend of decreasing pH (due to the accumulation of  $\rm CO_2$  in atmosphere and consequent mass transfer to the ocean) in the euphotic zone, in deeper water, the supplied organic carbon may lower the pH in a small degree. Third, the stimulation of biomass productivity results in a redistribution of nutrients at global scale; some areas will experience a reduction of nutrient supply, leading the decrease the biological productivity and consequently the decrease of economic activities, such as fisheries.

**Table 6**Atmospheric carbon capture by microalgae.

Strain	Experimental setup	$\mu$ $(d^{-1})$	$BP \\ (g \cdot L^{-1} \cdot d^{-1})$	$CO_2$ removal $(g \cdot L^{-1} \cdot d^{-1})$	Ref.
Acutodesmus sp.	OM: batch; R: LPDE; T = 30 °C; V = 1.2 L; LI = 30 $\mu E$ $m^{-2}$ s $^{-1}$ ; LDR = 16:8; CT = 16 d.	0.176	0.032	0.047	Swarnalatha et al. (2015)
Anabaena sp.	OM: batch; R: airlift; $T = 30 ^{\circ}\text{C}$ ; $V = 1.4 \text{L}$ ; $LI = 120 \mu\text{E} \text{m}^{-2} \text{s}^{-1}$ ; $CT = 9 \text{d}$ .	0.87		0.364	Nayak and Das (2013)
Anabaena sp.	OM: batch; R: bubble column; $T = 30$ °C; $V = 1.4$ L; $LI = 120 \mu\text{E} \text{m}^{-2} \text{s}^{-1}$ ; $CT = 9 \text{d}$ .	0.45		0.28	Nayak and Das (2013)
Anabaena sp.	OM: batch; R: bubble column; $T=27~^{\circ}\text{C}$ ; $V=1.8~\text{L}$ ; $LI=900~\mu\text{E}~\text{m}^{-2}~\text{s}^{-1}$ .			1.45	González López et al. (2009)
Chlorella kessleri	OM: batch; R: conic flasks; T = 30 °C; V = 2 L; LI = 3200 Lux (40 W); LDR = 12:12; CT = 20 d.	0.257	0.090		de Morais and Costa (2007b)
Chlorella vulgaris	OM: batch; R: tubular PBR; $T = 25$ °C; $V = 250$ L; $LI = 130 \mu\text{mol} \cdot \text{m}^{-2} \cdot \text{s}^{-1}$ .		0.4	0.075	Scragg et al. (2002)
Haematococcus pluvialis	OM: continuous; R: tubular PBR; $T = 16-18$ °C.	0.25	0.076	0.143	Huntley and Redalje (2007)
Nannochlorophsis oculata	OM: batch; R: cylindrical PBR; T = 26 °C; V = 0.8 L; LI = 300 $\mu mol \cdot m^{-2} \cdot s^{-1}$ ; CT = 6 d.	0.194	0.268		Chiu et al. (2009)
Nannochlorophsis oculata	OM: semi-continuous.	0.571	0.480		Chiu et al. (2009)
Scenedesmus dimorphus	OM: batch; R: LPDE; T = 25 °C; V = 1.5 L; LI = 300 $\mu E$ m <sup>-2</sup> s <sup>-1</sup> ; LDR = 14:10.	0.053	0.037	0.062	Vidyashankar et al. (2013)
Scenedesmus obliquus	OM: batch; R: column PBR; T = 30 °C; V = 2 L; LI = 3200 Lux (40 W); LDR = 12:12; CT = 21 d.	0.15	0.04		de Morais and Costa (2007a)
Spirulina sp.	OM: batch; R: column PBR; T = 30 °C; V = 1.8 L; LI = 3200 Lux; LDR = 12:12; CT = 21 d.	0.33	0.14		de Morais and Costa (2007a)

 $OM-Operation\ mode; T-temperature; R-reactor; \mu-specific\ growth\ rate; BP-biomass\ productivity; V-reactor\ volume; LI-light\ intensity; LDR-light\ dark\ ratio; CT-cultivation\ time; PBR-photobioreactor; LPDE-low\ density\ polyethylene.$ 

## 4.3. Algae (seaweed and microalgae) culture

A promising technology for CO<sub>2</sub> capture is the culture of microalgae. They are microorganisms, presenting a photosynthetic efficiency ten times higher than plants (Kumar et al., 2010; Pires et al., 2012). Microalgae can assimilate carbon from different sources: (i) atmospheric CO<sub>2</sub>; (ii) CO<sub>2</sub> from flue gases; and (iii) dissolved carbonates in the culture medium. In addition, microalgal biomass has several applications, including energy, food and feed production. However, its culture is still not economically attractive (current large-scale production is only for high-value products). Research studies are required, mainly concerning process integration (e.g. CO<sub>2</sub> capture, wastewater treatment, energy production, biorefinery approach) and photobioreactor design (to increase the biomass areal productivity, enhancing the photosynthetic efficiency of these systems).

Microalgal culture was studied for atmospheric CO<sub>2</sub> capture (Pires et al., 2014) and from flue gases (Doucha et al., 2005). Flue gases contain toxic compounds (NO<sub>x</sub> and SO<sub>x</sub>), which dissolution in the culture medium acidifies it, reducing microalgal growth. On the other hand, the cultivation of microalgae with atmospheric CO<sub>2</sub> has several advantages: (i) flexible location of microalgal farm, which enables the development of a biorefinery close to farm; and (ii) unnecessary CO<sub>2</sub> transportation infrastructure. Table 6 shows the results of atmospheric carbon capture by microalgae. Feeding microalgae with low CO<sub>2</sub> concentrated gaseous stream may limit microalgal growth. Taking into account this limitation, Brilman et al. (2013) integrated a unit for atmospheric CO<sub>2</sub> capture (TSA) with the culture of *Desmodesmus* sp. TSA unit concentrated CO<sub>2</sub> in gaseous stream, enhancing microalgal growth. At same time, TSA unit did not need to obtain high purity CO2 stream (that may also have a negative effect on microalgal culture); thus, the sorbent regeneration can be performed at lower temperatures (70–80 °C instead of 100 °C), reducing the operational costs of this unit.

Seaweeds also present high  $CO_2$  capture rates, showing gross primary productivities of  $1600~g_C \cdot m^{-2} \cdot yr^{-1}$  (Duarte et al., 2005) that is one order of magnitude higher than net primary productivity of crop land (470  $g_C \cdot m^{-2} \cdot yr^{-1}$ ). In addition, seaweed culture (in other words, ocean macroalgal afforestation – OMA) has significant advantages over terrestrial cultures in terms of their low land use, freshwater and fertilizers requirements (Moreira and Pires, 2016; N'Yeurt et al., 2012). OMA has a great potential to reduce atmospheric  $CO_2$ 

concentrations and the resultant biomass can be harvested to produce bioenergy from different conversion processes. For instance, OMA covering about 9% of the world's ocean surface can provide biomass for biomethane production that is sufficient to replace all of the required fossil fuel energy, removing simultaneously 53 Gt  $\rm CO_2$  per year from atmosphere.

## 4.4. Bioenergy with carbon capture and storage

As referred in the sections above, atmospheric CO<sub>2</sub> is naturally captured by plants and microorganisms through photosynthesis, producing biomass. The biomass can be then used to produce electricity in a thermoelectric power plant. Therefore, biomass is considered clean energy source, representing a zero-emission technology. If CCS technology is applied to biomass power plant, CO<sub>2</sub> captured by photosynthesis is not emitted to atmosphere and consequently the carbon balance is negative. BECCS can contribute in reduction of atmospheric CO<sub>2</sub> concentration, converting the energy sector into a net carbon sink (Keith, 2009; McLaren, 2012; Obersteiner et al., 2001). The biomass combustion is applied for production of electricity and not all heat is recovered. Bui et al. (2017) studied the recovery of waste heat in amine-based CO<sub>2</sub> capture. This integration may improve the energy efficiency of the BECCS process, as power plant steam is not required to regenerate the absorbent. Besides combustion processes, ethanol fermentation or black liquor (wood pulp effluent) gasification with CO<sub>2</sub> capture are also considered as NETs (Rhodes, 2007). Moreira et al. (2016) studied the production of ethanol and electricity from sugar cane, bagasse and other residues of Brazil, taking into account the process carbon balance and cost. In the studied production process, CO<sub>2</sub> capture is performed twice: in fermentation and in electricity generation. To be economically viable process, the blended gasoline (with produced ethanol) should increase its cost by  $0.066\$ \cdot l^{-1}$ .

BECCS presents also some disadvantages. Biomass presents higher moisture content and a lower heating value comparing with coal (but has low  $SO_x$  and  $NO_x$  emissions). Moreover, impact assessment scenarios (that include BECCS) assume the application of this technology at a scale which deployment is highly uncertain (Fuss et al., 2014; Naomi and Clair, 2016). Bioenergy use is currently used at a lower scale in some demonstration projects. However, to remove gigatonne of carbon, large areas of land are required (1-1.7) ha of land for each tonne of

**Table 7**Studies concerning NETs projects

Project	Focus areas	References
AVOID	Integrated assessment models	Warren et al. (2013), Arnell et al. (2016), O'Neill et al. (2016), Gambhir et al. (2017a), Gambhir et al. (2017b), Lowe et al. (2017), Napp et al. (2017), Good et al. (2018).
SUCCESS	Soil mineralization	Renforth et al. (2009), Renforth et al. (2011), Schmidt et al. (2011), Renforth and Manning (2011), Washbourne et al. (2012), Manning and Renforth (2013), Manning et al. (2013), Washbourne et al. (2015).
IAGP	Assessing effectiveness of geoengineering proposals	Crook et al. (2011), Jones and Haywood (2012), Jarvis et al. (2012), Bellamy et al. (2012), Jenkins et al. (2013), Haywood et al. (2013), Pidgeon et al. (2013), Stuart et al. (2013), Scott et al. (2014), Windeatt et al. (2014)
SOLAS	Interactions between ocean and atmosphere	Law et al. (2013), Boyd et al. (2004), Law et al. (2011), Williamson et al. (2012), Guieu et al. (2014), Bell et al. (2015), Smith et al. (2018).
NER Negative CO <sub>2</sub>	Bio-chemical-looping combustion	Ryden et al. (2017), Vilches et al. (2017).
Global Carbon Project	Interaction between carbon and other biogeochemical cycles	Falkowski et al. (2000), Schimel et al. (2001), Gullison et al. (2007), Raupach et al. (2007), Canadell et al. (2007), Canadell and Raupach (2008), Le Quere et al. (2009), Friedlingstein et al. (2010), Pan et al. (2011), Peters et al. (2011), Peters et al. (2011), Le Quere et al. (2013), Kirschke et al. (2013), Poulter et al. (2014), Fuss et al. (2014), Raupach et al. (2014), Smith et al. (2016), Tian et al. (2016), Zhu et al. (2016).
SOLETAIR	Hydrocarbon production with captured CO <sub>2</sub>	Elfving et al. (2017).

removed carbon). Moreover, CCS is still not commercially established. One of the most concerning issue is the safety regarding  $\rm CO_2$  storage (mainly with social acceptance).

# 4.5. Biochar

The most interesting CO<sub>2</sub> biosequestration process is the recycling of part of biomass in the form of biochar. Biochar is produced by the combustion of biomass in a low-zero oxygen environment (pyrolysis or gasification). Feedstocks for these thermochemical processes could be agriculture residues, wood chip, energy crops, organic waste and algae (microalgae and seaweed) (Bird et al., 2011; Buss et al., 2016; Windeatt et al., 2014). Biomass is converted to: (i) a gaseous fraction applied to production of energy; and (ii) biochar that is highly stable and resistant to biodegradation. The physicochemical characteristics of biochar depend on the biomass feedstock nature and the thermochemical conversion conditions. This process can avoid the return of biotic carbon to atmosphere if biochar is land filled or used to enrich agricultural land. Adding biochar to the soil is associated to the increase of crop yields due to the enhancement of soil chemical characteristics (increase of total organic carbon and cation exchange capacity) and water retention (Mathews, 2008; Mohan et al., 2018). Currently, biomass residues are burned or decomposed in soil; thus, most of the carbon captured by photosynthesis is then emitted to the atmosphere. Converting biomass to biochar (for soil amendment) may reduce the CO<sub>2</sub> emissions by 1.8 Gt·yr $^{-1}$  even without CCS (Mattila et al., 2012). In addition, carbon in biochar can persist in soils from decades to millennia. Kuppusamy et al. (2016) described in their study the potential benefits, hazards, and negative implications of biochar.

## 5. Main research projects

Main research projects focusing negative emission technologies have been developed in EU countries, which have the leadership on climate change mitigation. The study of the interactions between atmosphere, land and ocean were studied, as well as the consequences of climate change (scenarios modelling). Table 7 presents a compilation of the published works regarding these projects.

#### 6. Current and future economic and technical challenges

If the climate policies require the deployment of NETs to meet the COP21 target (1.5 and 2  $^{\circ}$ C), important issues should be addressed, including economic incentives to early deployment (e.g. setting a price of CO<sub>2</sub>, providing subsidies or defining regulations), associated markets, scale-up and public acceptance (crucial for the new technologies adoption).

In physicochemical processes of CO<sub>2</sub> capture, the reduction of energy requirement for sorbent regeneration should be analysed. The design of scrubbing towers should be enhanced to reduce the size and its cost. Due to the availability and risk of CO<sub>2</sub> storage sites, research studies should focus on the chemical conversion of captured CO<sub>2</sub> to chemicals (including fuels). The use of excess of renewable energy (solar and wind) for fuel production should be explored. Regarding ocean alkalinity enhancement and fertilization, it is important to understand the consequences of these actions on the marine ecosystems. Research studies should find the reason why unexpected results were achieved in ocean fertilization with phosphorus.

To avoid high costs in the capture and purification of CO<sub>2</sub> in direct air capture, the resulting gaseous stream can be applied for microalgae culture. For this application, 5-15% (v/v) of CO<sub>2</sub> gaseous stream usually corresponds to the highest growth rates for a wide range of species. Microalgae have productivities with one or two orders of magnitude higher than terrestrial plants. Their biomass can be used to produce bioenergy, emitting CO<sub>2</sub> at higher concentration that can be easily captured by physicochemical processes. In addition, cultivation system design is of greatest importance to achieve higher biomass productivities (corresponding to high carbon uptake rates). Concerning BECCS, this technology could be applied in sugar and paper processing industries, as well as in industrial and municipal waste management. It represents the most ready NET to be deployed and can be a buffer for the emissions of sectors where reductions are difficult to achieve (diffuse emission sources). The main economic and technical challenges are associated to the sustainability of the scale-up (biomass supply chain) and the technical barriers regarding biomass conversion process (e.g. high moisture content, variability and impurities of biomass, promoting the corrosion and fouling). The intensification of bioenergy production may lead to a high pressure on natural resources (land and water). Research about negative impacts of biomass production on soil quality, availability of water and biodiversity should be performed. Moreover, the selection of biomass feedstock that avoids high processing and minimizes the modifications in the conversion (and air pollution control) equipment should be studied. In addition, the heat integration should be performed between the biomass conversion unit and CO<sub>2</sub> capture unit, to decrease the energy requirements. The CCS technology deployment and social acceptance are critical for the application of BECCS at large scale. The future study of biochar should focus on the stability of carbon and its interactions in different environments. Regarding production and quality standards, the pyrolysis process should be analysed to infer the effect of temperature and time duration of the process in biochar yield and stability. Additionally, the effect of biochar in soil should be understood.

## 7. Conclusions

Despite its very low concentration, CO<sub>2</sub> capture from atmosphere may be feasible. This paper presents the current state of art of the main NETs. The integration of the technologies (physicochemical and biological) may reduce the overall costs of the process. It is important to highlight that negative emissions should be taken into account as a complementary technology to achieve the climate targets. NETs should be tested at the scale modelled in different scenarios and their environmental impacts should be fully understood to help in the definition of climate change mitigation policies.

## Acknowledgements

This work was financially supported by: (i) Project UID/EQU/00511/2019 - Laboratory for Process Engineering, Environment, Biotechnology and Energy – LEPABE funded by national funds through FCT/MCTES (PIDDAC); and (ii) Project POCI-01-0145-FEDER-031736 – PIV4Algae – Process Intensification for microalgal production and Valorisation, funded by FEDER funds through COMPETE2020 – Programa Operacional Competitividade e Internacionalização (POCI) and by national funds (PIDDAC) through FCT/MCTES. J.C.M. Pires acknowledges the FCT Investigator 2015 Programme (IF/01341/2015).

## References

- Allen, M.R., Frame, D.J., Huntingford, C., Jones, C.D., Lowe, J.A., Meinshausen, M., et al., 2009. Warming caused by cumulative carbon emissions towards the trillionth tonne. Nature 458, 1163–1166.
- Archer, D., Eby, M., Brovkin, V., Ridgwell, A., Cao, L., Mikolajewicz, U., et al., 2009. Atmospheric lifetime of fossil fuel carbon dioxide. Annu. Rev. Earth Planet. Sci. 37, 117–134.
- Arnell, N.W., Brown, S., Gosling, S.N., Hinkel, J., Huntingford, C., Lloyd-Hughes, B., et al., 2016. Global-scale climate impact functions: the relationship between climate forcing and impact. Clim. Chang. 134, 475–487.
- Aumont, O., Bopp, L., 2006. Globalizing results from ocean in situ iron fertilization studies.

  Glob. Biogeochem. Cycles 20.
- Azar, C., Lindgren, K., Larson, E., Mollersten, K., 2006. Carbon capture and storage from fossil fuels and biomass costs and potential role in stabilizing the atmosphere. Clim. Chang. 74. 47–79.
- Azar, C., Johansson, D.J.A., Mattsson, N., 2013. Meeting global temperature targets-the role of bioenergy with carbon capture and storage. Environ. Res. Lett. 8.
- Baciocchi, R., Storti, G., Mazzotti, M., 2006. Process design and energy requirements for the capture of carbon dioxide from air. Chem. Eng. Process. 45, 1047–1058.
- Bell, T.G., De Bruyn, W., Marandino, C.A., Miller, S.D., Law, C.S., Smith, M.J., et al., 2015. Dimethylsulfide gas transfer coefficients from algal blooms in the Southern Ocean. Atmos. Chem. Phys. 15, 1783–1794.
- Bellamy, R., Chilvers, J., Vaughan, N.E., Lenton, T.M., 2012. A review of climate geoengineering appraisals. Wiley Interdiscip. Rev. Clim. Chang. 3, 597–615.
- Belmabkhout, Y., Serna-Guerrero, R., Sayari, A., 2010. Amine-bearing mesoporous silica for CO2 removal from dry and humid air. Chem. Eng. Sci. 65, 3695–3698.
- Belmabkhout, Y., Guillerm, V., Eddaoudi, M., 2016. Low concentration CO2 capture using physical adsorbents: are metal-organic frameworks becoming the new benchmark materials? Chem. Eng. J. 296, 386–397.Bhatt, P.M., Belmabkhout, Y., Cadiau, A., Adil, K., Shekhah, O., Shkurenko, A., et al., 2016. A
- Bhatt, P.M., Belmabkhout, Y., Cadiau, A., Adil, K., Shekhah, O., Shkurenko, A., et al., 2016. A fine-tuned fluorinated MOF addresses the needs for trace CO2 removal and air capture using physisorption. J. Am. Chem. Soc. 138, 9301–9307.
- Bird, M.I., Wurster, C.M., Silva, P.H.D., Bass, A.M., de Nys, R., 2011. Algal biochar production and properties. Bioresour. Technol. 102, 1886–1891.
- Boucher, J.F., Tremblay, P., Gaboury, S., Villeneuve, C., 2012. Can boreal afforestation help offset incompressible GHG emissions from Canadian industries? Process. Saf. Environ. Prot. 90, 459–466.
- Boyd, P.W., Law, C.S., Wong, C.S., Nojiri, Y., Tsuda, A., Levasseur, M., et al., 2004. The decline and fate of an iron-induced subarctic phytoplankton bloom. Nature 428, 549–553.
- Boyd, P.W., Jickells, T., Law, C.S., Blain, S., Boyle, E.A., Buesseler, K.O., et al., 2007. Mesoscale iron enrichment experiments 1993–2005: synthesis and future directions. Science 315, 612–617.
- Brilman, W., Alba, L.G., Veneman, R., 2013. Capturing atmospheric CO2 using supported amine sorbents for microalgae cultivation. Biomass Bioenergy 53, 39–47.
- Bui, M., Fajardy, M., Mac Dowell, N., 2017. Bio-Energy with CCS (BECCS) performance evaluation: efficiency enhancement and emissions reduction. Appl. Energy 195, 289–302.
- Buss, W., Graham, M.C., Shepherd, J.G., Masek, O., 2016. Suitability of marginal biomassderived biochars for soil amendment. Sci. Total Environ. 547, 314–322.
- Canadell, J.G., Raupach, M.R., 2008. Managing forests for climate change mitigation. Science 320, 1456–1457.
- Canadell, J.G., Le Quere, C., Raupach, M.R., Field, C.B., Buitenhuis, E.T., Ciais, P., et al., 2007. Contributions to accelerating atmospheric CO(2) growth from economic activity,

- carbon intensity, and efficiency of natural sinks. Proc. Natl. Acad. Sci. U. S. A. 104, 18866–18870.
- Cao, L., Caldeira, K., 2010. Can ocean iron fertilization mitigate ocean acidification? Clim. Chang. 99, 303–311.
- Change IPoC, 2013. Working Group I contribution 416 to the IPCC Fifth Assessment Report. Climate Change 2013: The Physical Science Basis Summary for Policymakers.
- Chiu, S.-Y., Kao, C.-Y., Tsai, M.-T., Ong, S.-C., Chen, C.-H., Lin, C.-S., 2009. Lipid accumulation and CO2 utilization of Nannochloropsis oculata in response to CO2 aeration.
- Choi, S., Drese, J.H., Eisenberger, P.M., Jones, C.W., 2011. Application of amine-tethered solid sorbents for direct CO2 capture from the ambient air. Environ. Sci. Technol. 45, 2420–2427
- Crombie, K., Masek, O., 2015. Pyrolysis biochar systems, balance between bioenergy and carbon sequestration. Glob. Change Biol. Bioenergy. 7, 349–361.
- Crook, J.A., Jones, L.A., Forster, P.M., Crook, R., 2011. Climate change impacts on future photovoltaic and concentrated solar power energy output. Energy Environ. Sci. 4, 3101–3109.
- Dawson, T.P., Jackson, S.T., House, J.I., Prentice, I.C., Mace, G.M., 2011. Beyond predictions: biodiversity conservation in a changing climate. Science 332, 53–58.
- Diego, M.E., Alonso, M., 2016. Operational feasibility of biomass combustion with in situ CO2 capture by CaO during 360 h in a 300 kW(th) calcium looping facility. Fuel 181. 325–329.
- Doney, S.C., Fabry, V.J., Feely, R.A., Kleypas, J.A., 2009. Ocean acidification: the other CO2 problem. Annu. Rev. Mar. Sci. 1, 169–192.
- Doucha, J., Straka, F., Livansky, K., 2005. Utilization of flue gas for cultivation of microalgae (Chlorella sp.) in an outdoor open thin-layer photobioreactor. J. Appl. Phycol. 17, 403–412.
- Dovi, V.G., Friedler, F., Huisingh, D., Klemes, J.J., 2009. Cleaner energy for sustainable future. J. Clean. Prod. 17, 889–895.
- Duarte, C.M., Middelburg, J.J., Caraco, N., 2005. Major role of marine vegetation on the oceanic carbon cycle. Biogeosciences 2, 1–8.
- Edwards, D.P., Lim, F., James, R.H., Pearce, C.R., Scholes, J., Freckleton, R.P., et al., 2017. Climate change mitigation: potential benefits and pitfalls of enhanced rock weathering in tropical agriculture. Biol. Lett. 13.
- Elfving, J., Bajamundi, C., Kauppinen, J., Sainio, T., 2017. Modelling of equilibrium working capacity of PSA, TSA and TVSA processes for CO2 adsorption under direct air capture conditions. J. CO<sub>2</sub> Util. 22, 270–277.
- Ellison, D., Morris, C.E., Locatelli, B., Sheil, D., Cohen, J., Murdiyarso, D., et al., 2017. Trees, forests and water: cool insights for a hot world. Glob. Environ. Chang. 43, 51–61.
- Falkowski, P., Scholes, R.J., Boyle, E., Canadell, J., Canfield, D., Elser, J., et al., 2000. The global carbon cycle: a test of our knowledge of earth as a system. Science 290, 291–296.
- Farrelly, D.J., Everard, C.D., Fagan, C.C., McDonnell, K.P., 2013. Carbon sequestration and the role of biological carbon mitigation: a review. Renew. Sust. Energ. Rev. 21, 712–727
- Friedlingstein, P., Houghton, R.A., Marland, G., Hackler, J., Boden, T.A., Conway, T.J., et al., 2010. Update on CO2 emissions. Nat. Geosci. 3, 811–812.
- Fuss, S., Canadell, J.G., Peters, G.P., Tavoni, M., Andrew, R.M., Ciais, P., et al., 2014. Commentary: betting on negative emissions. Nat. Clim. Chang. 4, 850–853.
- Fuss, S., Lamb, W.F., Callaghan, M.W., Hilaire, J., Creutzig, F., Amann, T., et al., 2018. Negative emissions-part 2: costs, potentials and side effects. Environ. Res. Lett. 13.
- Gambhir, A., Drouet, L., McCollum, D., Napp, T., Bernie, D., Hawkes, A., et al., 2017a. Assessing the feasibility of global long-term mitigation scenarios. Energies 10.
- Gambhir, A., Napp, T., Hawkes, A., Hoglund-Isaksson, L., Winiwarter, W., Purohit, P., et al., 2017b. The contribution of non-CO2 greenhouse gas mitigation to achieving longterm temperature goals. Energies 10.
- Gasser, T., Guivarch, C., Tachiiri, K., Jones, C.D., Ciais, P., 2015. Negative emissions physically needed to keep global warming below 2 degrees C. Nat. Commun. 6.
- Gebald, C., Wurzbacher, J.A., Tingaut, P., Zimmermann, T., Steinfeld, A., 2011. Amine-based nanofibrillated cellulose as adsorbent for CO2 capture from air. Environ. Sci. Technol. 45. 9101–9108.
- Gebald, C., Wurzbacher, J.A., Tingaut, P., Steinfeld, A., 2013. Stability of amine-functionalized cellulose during temperature-vacuum-swing cycling for CO2 capture from air. Environ. Sci. Technol. 47, 10063–10070.
- GISS, 2018. Surface Temperature Analysis. 2018. National Aeronautics and Space Administration Goddard Institute for Space Studies.
- Goeppert, A., Czaun, M., May, R.B., Prakash, G.K.S., Olah, G.A., Narayanan, S.R., 2011. Carbon dioxide capture from the air using a polyamine based regenerable solid adsorbent. J. Am. Chem. Soc. 133, 20164–20167.
- Goeppert, A., Czaun, M., Prakash, G.K.S., Olah, G.A., 2012. Air as the renewable carbon source of the future: an overview of CO2 capture from the atmosphere. Energy Environ. Sci. 5, 7833–7853.
- Goeppert, A., Zhang, H., Czaun, M., May, R.B., Prakash, G.K.S., Olah, G.A., et al., 2014. Easily regenerable solid adsorbents based on polyamines for carbon dioxide capture from the air. Chemsuschem 7, 1386–1397.
- González López, C.V., Acién Fernández, F.G., Fernández Sevilla, J.M., Sánchez Fernández, J.F., Cerón García, M.C., Molina Grima, E., 2009. Utilization of the cyanobacteria Anabaena sp. ATCC 33047 in CO2 removal processes. Bioresour. Technol. 100, 5904–5910.
- Good, P., Bamber, J., Halladay, K., Harper, A.B., Jackson, L.C., Kay, G., et al., 2018. Recent progress in understanding climate thresholds: ice sheets, the Atlantic meridional overturning circulation, tropical forests and responses to ocean acidification. Progress in Physical Geography: Earth and Environment 42, 24–60.
- Guieu, C., Aumont, O., Paytan, A., Bopp, L., Law, C.S., Mahowald, N., et al., 2014. The significance of the episodic nature of atmospheric deposition to low nutrient low chlorophyll regions. Glob. Biogeochem. Cycles 28, 1179–1198.

- Gullison, R.E., Frumhoff, P.C., Canadell, J.G., Field, C.B., Nepstad, D.C., Hayhoe, K., et al., 2007. Tropical forests and climate policy. Science 316, 985–986.
- Harrison, D.P., 2017. Global negative emissions capacity of ocean macronutrient fertilization. Environ. Res. Lett. 12.
- Haywood, J.M., Jones, A., Bellouin, N., Stephenson, D., 2013. Asymmetric forcing from stratospheric aerosols impacts Sahelian rainfall. Nat. Clim. Chang. 3, 660–665.
- Hoegh-Guldberg, O., Mumby, P.J., Hooten, A.J., Steneck, R.S., Greenfield, P., Gomez, E., et al., 2007. Coral reefs under rapid climate change and ocean acidification. Science 318, 1737–1742
- Huntley, M.E., Redalje, D.G., 2007. CO2 mitigation and renewable oil from photosynthetic microbes: a new appraisal. Mitig. Adapt. Strateg. Glob. Chang. 12, 573-608.
- microbes: a new appraisal. Mitig. Adapt. Strateg. Glob. Chang. 12, 573–608. Inagaki, F., Matsumoto, C., Iwata, T., Mukai, C., 2017. CO2-selective absorbents in air: reverse lipid bilayer structure forming neutral carbamic acid in water without hydration. L. Am. Chem. Soc. 139, 4639–4642.
- Jarvis, A.J., Leedal, D.T., Hewitt, C.N., 2012. Climate-society feedbacks and the avoidance of dangerous climate change. Nat. Clim. Chang. 2, 668–671.
- Jenkins, A.K.L., Forster, P.M., Jackson, L.S., 2013. The effects of timing and rate of marine cloud brightening aerosol injection on albedo changes during the diurnal cycle of marine stratocumulus clouds. Atmos. Chem. Phys. 13, 1659–1673.
- Jones, C.W., 2011. CO2 capture from dilute gases as a component of modern global carbon management. Annu. Rev. Chem. Biomol. Eng. 2 (2), 31–52.
- Jones, A., Haywood, J.M., 2012. Sea-spray geoengineering in the HadGEM2-ES earthsystem model: radiative impact and climate response. Atmos. Chem. Phys. 12, 10887–10898.
- Jones, C.D., Ciais, P., Davis, S.J., Friedlingstein, P., Gasser, T., Peters, G.P., et al., 2016. Simulating the earth system response to negative emissions. Environ. Res. Lett. 11.
- Kato, E., Moriyama, R., Kurosawa, A., 2017. A sustainable pathway of bioenergy with carbon capture and storage deployment. 13th International Conference on Greenhouse Gas Control Technologies. vol. 114, pp. 6115–6123 Ghgt-13.
- Keith, D.W., 2009. Why capture CO2 from the atmosphere? Science 325, 1654-1655.
- Keith, D.W., Ha-Duong, M., Stolaroff, J.K., 2006. Climate strategy with CO2 capture from the air. Clim. Chang. 74, 17–45.
- Keller, J.K., White, J.R., Bridgham, S.D., Pastor, J., 2004. Climate change effects on carbon and nitrogen mineralization in peatlands through changes in soil quality. Glob. Chang. Biol. 10, 1053–1064.
- Kemper, J., 2015. Biomass and carbon dioxide capture and storage: a review. Int. J. Greenhouse Gas Control 40, 401–430.
- Kindermann, G., Obersteiner, M., Sohngen, B., Sathaye, J., Andrasko, K., Rametsteiner, E., et al., 2008. Global cost estimates of reducing carbon emissions through avoided deforestation. Proc. Natl. Acad. Sci. U. S. A. 105, 10302–10307.
- Kirschke, S., Bousquet, P., Ciais, P., Saunois, M., Canadell, J.G., Dlugokencky, E.J., et al., 2013. Three decades of global methane sources and sinks. Nat. Geosci. 6, 813–823.
- Kohler, P., Hartmann, J., Wolf-Gladrow, D.A., 2010. Geoengineering potential of artificially enhanced silicate weathering of olivine. Proc. Natl. Acad. Sci. U. S. A. 107, 20228–20233.
- Krevor, S.C.M., Lackner, K.S., 2011. Enhancing serpentine dissolution kinetics for mineral carbon dioxide sequestration. Int. J. Greenhouse Gas Control 5, 1073–1080.
- Krom, M.D., Thingstad, T.F., Brenner, S., Carbo, P., Drakopoulos, P., Fileman, T.W., et al., 2005. Summary and overview of the CYCLOPS P addition Lagrangian experiment in the Eastern Mediterranean. Deep-Sea Res. II Top. Stud. Oceanogr. 52, 3090–3108.
- Kumar, A., Ergas, S., Yuan, X., Sahu, A., Zhang, Q.O., Dewulf, J., et al., 2010. Enhanced CO2 fixation and biofuel production via microalgae: recent developments and future directions. Trends Biotechnol. 28, 371–380.
- Kuppusamy, S., Thavamani, P., Megharaj, M., Venkateswarlu, K., Naidu, R., 2016. Agronomic and remedial benefits and risks of applying biochar to soil: current knowledge and future research directions. Environ. Int. 87, 1–12.
- Lackner, K.S., 2002. Carbonate chemistry for sequestering fossil carbon. Annu. Rev. Energy Environ. 27, 193–232.
- Lackner, K.S., 2009. Capture of carbon dioxide from ambient air. Eur. Phys. J. Spec. Top. 176, 93–106.
- Lackner, K.S., Brennan, S., 2009. Envisioning carbon capture and storage: expanded possibilities due to air capture, leakage insurance, and C-14 monitoring. Clim. Chang. 96, 357–378.
- Lackner, K.S., Brennan, S., Matter, J.M., Park, A.H.A., Wright, A., van der Zwaan, B., 2012. The urgency of the development of CO2 capture from ambient air. Proc. Natl. Acad. Sci. U. S. A. 109, 13156–13162.
- Lal, R., Griffin, M., Apt, J., Lave, L., Morgan, M.G., 2004. Ecology-managing soil carbon. Science 304, 393.
- Lampitt, R.S., Achterberg, E.P., Anderson, T.R., Hughes, J.A., Iglesias-Rodriguez, M.D., Kelly-Gerreyn, B.A., et al., 2008. Ocean fertilization: a potential means of geoengineering? Philos. Trans. R. Soc. A Math. Phys. Eng. Sci. 366, 3919–3945.
- Larkin, A., Kuriakose, J., Sharmina, M., Anderson, K., 2018. What if negative emission technologies fail at scale? Implications of the Paris Agreement for big emitting nations. Clim. Pol. 18, 690–714.
- Law, C.S., Woodward, E.M.S., Ellwood, M.J., Marriner, A., Bury, S.J., Safi, K.A., 2011. Response of surface nutrient inventories and nitrogen fixation to a tropical cyclone in the southwest Pacific. Limnol. Oceanogr. 56, 1372–1385.
- Law, C.S., Breviere, E., de Leeuw, G., Garcon, V., Guieu, C., Kieber, D.J., et al., 2013. Evolving research directions in Surface Ocean-Lower Atmosphere (SOLAS) science. Environ. Chem. 10 (1), 16.
- Le Quere, C., Raupach, M.R., Canadell, J.G., Marland, G., Bopp, L., Ciais, P., et al., 2009. Trends in the sources and sinks of carbon dioxide. Nat. Geosci. 2, 831–836.
- Le Quere, C., Andres, R.J., Boden, T., Conway, T., Houghton, R.A., House, J.I., et al., 2013. The global carbon budget 1959–2011. Earth Syst. Sci. Data 5, 165–185.
- Le Quere, C., Andrew, R.M., Friedlingstein, P., Sitch, S., Hauck, J., Pongratz, J., et al., 2018. Global carbon budget 2018. Earth Syst. Sci. Data 10, 2141–2194.

- Liu, S.W., Zhang, Y.J., Zong, Y.J., Hu, Z.Q., Wu, S., Zhou, J., et al., 2016. Response of soil carbon dioxide fluxes, soil organic carbon and microbial biomass carbon to biochar amendment; a meta-analysis. Glob. Change Biol. Bioenergy, 8, 392–406.
- Lorenz, K., Lal, R., 2014a. Biochar application to soil for climate change mitigation by soil organic carbon sequestration. J. Plant Nutr. Soil Sci. 177, 651–670.
- Lorenz, K., Lal, R., 2014b. Soil organic carbon sequestration in agroforestry systems. A review. Agron. Sustain. Dev. 34, 443–454.
- Lowe, J.A., Arnell, N.W., Warren, R., Gambhir, A.J., Bernie, D., Thompson, E., 2017. Avoiding dangerous climate: results from the AVOID2 programme. Weather 72, 340–U80.
- Lu, W.G., Sculley, J.P., Yuan, D.Q., Krishna, R., Zhou, H.C., 2013. Carbon dioxide capture from air using amine-grafted porous polymer networks. J. Phys. Chem. C 117, 4057-4061
- Manning, D.A.C., Renforth, P., 2013. Passive sequestration of atmospheric CO2 through coupled plant-mineral reactions in urban soils. Environ. Sci. Technol. 47, 135–141
- Manning, D.A.C., Renforth, P., Lopez-Capel, E., Robertson, S., Ghazireh, N., 2013. Carbonate precipitation in artificial soils produced from basaltic quarry fines and composts: an opportunity for passive carbon sequestration. Int. J. Greenhouse Gas Control 17, 309–317.
- Marland, G., West, T.O., Schlamadinger, B., Canella, L., 2003. Managing soil organic carbon in agriculture: the net effect on greenhouse gas emissions. Tellus Ser. B Chem. Phys. Meteorol. 55, 613–621.
- Mathews, J.A., 2008. Carbon-negative biofuels. Energy Policy 36, 940-945.
- Mattila, T., Gronroos, J., Judi, J., Korhonen, M.R., 2012. Is biochar or straw-bale construction a better carbon storage from a life cycle perspective? Process. Saf. Environ. Prot. 90, 452–458
- Mazzotti, M., Baciocchi, R., Desmond, M.J., Socolow, R.H., 2013. Direct air capture of CO2 with chemicals: optimization of a two-loop hydroxide carbonate system using a countercurrent air-liquid contactor. Clim. Chang. 118, 119–135.
- McDonald, T.M., Lee, W.R., Mason, J.A., Wiers, B.M., Hong, C.S., Long, J.R., 2012. Capture of carbon dioxide from air and flue gas in the alkylamine-appended metal-organic framework mmen-Mg-2(dobpdc). J. Am. Chem. Soc. 134, 7056–7065.
- McLaren, D., 2012. A comparative global assessment of potential negative emissions technologies. Process. Saf. Environ. Prot. 90, 489–500.
- Meinshausen, M., Meinshausen, N., Hare, W., Raper, S.C.B., Frieler, K., Knutti, R., et al., 2009. Greenhouse-gas emission targets for limiting global warming to 2 degrees C. Nature 458, 1158–U96.
- Minx, J.C., Lamb, W.F., Callaghan, M.W., Bornmann, L., Fuss, S., 2017. Fast growing research on negative emissions. Environ. Res. Lett. 12.
- Minx, J.C., Lamb, W.F., Callaghan, M.W., Fuss, S., Hilaire, J., Creutzig, F., et al., 2018. Negative emissions-part 1: research landscape and synthesis. Environ. Res. Lett. 13.
- Mohan, D., Abhishek, K., Sarswat, A., Patel, M., Singh, P., Pittman, C.U., 2018. Biochar production and applications in soil fertility and carbon sequestration a sustainable solution to crop-residue burning in India. RSC Adv. 8, 508–520.
- de Morais, M.G., Costa, J.A.V., 2007a. Biofixation of carbon dioxide by Spirulina sp. and Scenedesmus obliquus cultivated in a three-stage serial tubular photobioreactor. J. Biotechnol. 129, 439–445.
- de Morais, M.G., Costa, J.A.V., 2007b. Isolation and selection of microalgae from coal fired thermoelectric power plant for biofixation of carbon dioxide. Energy Convers. Manag. 48, 2169–2173.
- Moreira, D., Pires, J.C.M., 2016. Atmospheric CO2 capture by algae: negative carbon dioxide emission path. Bioresour. Technol. 215, 371–379.
- Moreira, J.R., Romeiro, V., Fuss, S., Kraxner, F., Pacca, S.A., 2016. BECCS potential in Brazil: achieving negative emissions in ethanol and electricity production based on sugar cane bagasse and other residues. Appl. Energy 179, 55–63.
- Moss, R.H., Edmonds, J.A., Hibbard, K.A., Manning, M.R., Rose, S.K., van Vuuren, D.P., et al., 2010. The next generation of scenarios for climate change research and assessment. Nature 463, 747–756.
- Naomi, E.V., Clair, G., 2016. Expert assessment concludes negative emissions scenarios may not deliver. Environ. Res. Lett. 11, 095003.
- Napp, T., Bernie, D., Thomas, R., Lowe, J., Hawkes, A., Gambhir, A., 2017. Exploring the feasibility of low-carbon scenarios using historical energy transitions analysis. Energies 10.
- Nayak, B.K., Das, D., 2013. Improvement of carbon dioxide biofixation in a photobioreactor using Anabaena sp. PCC 7120. Process Biochem. 48, 1126–1132.
- Nemet, G.F., Callaghan, M.W., Creutzig, F., Fuss, S., Hartmann, J., Hilaire, J., et al., 2018. Negative emissions-part 3: innovation and upscaling. Environ. Res. Lett. 13.
- NOAA, 2018. GMD Measurement Locations. National Oceanic & Atmospheric Administration (NOAA), Earth System Research Laboratory, Global Monitoring Division.
- N'Yeurt, A.D., Chynoweth, D.P., Capron, M.E., Stewart, J.R., Hasan, M.A., 2012. Negative carbon via ocean afforestation. Process. Saf. Environ. Prot. 90, 467–474.

  Obersteiner, M., Azar, C., Kauppi, P., Mollersten, K., Moreira, J., Nilsson, S., et al., 2001. Man-
- aging climate risk. Science 294, 786–787. Obersteiner, M., Bottcher, H., Yamagata, Y., 2010. Terrestrial ecosystem management for
- Obersteiner, M., Bottcher, H., Yamagata, Y., 2010. Terrestrial ecosystem management for climate change mitigation. Curr. Opin. Environ. Sustain. 2, 271–276.
- O'Neill, B.C., Tebaldi, C., van Vuuren, D.P., Eyring, V., Friedlingstein, P., Hurtt, G., et al., 2016. The Scenario Model Intercomparison Project (ScenarioMIP) for CMIP6. Geosci. Model Dev. 9, 3461–3482.
- Orr, J.C., Fabry, V.J., Aumont, O., Bopp, L., Doney, S.C., Feely, R.A., et al., 2005. Anthropogenic ocean acidification over the twenty-first century and its impact on calcifying organisms. Nature 437, 681–686.
- Pan, Y.D., Birdsey, R.A., Fang, J.Y., Houghton, R., Kauppi, P.E., Kurz, W.A., et al., 2011. A large and persistent carbon sink in the world's forests. Science 333, 988–993.
- Paquay, F.S., Zeebe, R.E., 2013. Assessing possible consequences of ocean liming on ocean pH, atmospheric CO2 concentration and associated costs. Int. J. Greenhouse Gas Control 17, 183–188.

- Peters, G.P., Marland, G., Le Ouéré, C., Boden, T., Canadell, I.G., Raupach, M.R., 2011, Rapid growth in CO2 emissions after the 2008–2009 global financial crisis, Nat, Clim, Chang, 2. 2.
- Peters, G.P., Andrew, R.M., Boden, T., Canadell, I.G., Ciais, P., Le Ouere, C., et al., 2013, Commentary: the challenge to keep global warming below 2 degrees C. Nat. Clim. Chang.
- Pidgeon, N., Parkhill, K., Corner, A., Vaughan, N., 2013. Deliberating stratospheric aerosols for climate geoengineering and the SPICE project, Nat. Clim. Chang. 3, 451–457.
- Pielke, R.A., 2009. An idealized assessment of the economics of air capture of carbon dioxide in mitigation policy. Environ. Sci. Pol. 12, 216-225.
- Pires, J.C.M., Martins, F.G., Alvim-Ferraz, M.C.M., Simoes, M., 2011. Recent developments on carbon capture and storage: an overview. Chem. Eng. Res. Des. 89, 1446-1460.
- Pires, J.C.M., Alvim-Ferraz, M.C.M., Martins, F.G., Simoes, M., 2012. Carbon dioxide capture from flue gases using microalgae: engineering aspects and biorefinery concept. Renew. Sust. Energ. Rev. 16, 3043–3053.
- Pires, J.C.M., Goncalves, A.L., Martins, F.G., Alvim-Ferraz, M.C.M., Simoes, M., 2014. Effect of light supply on CO2 capture from atmosphere by Chlorella vulgaris and Pseudokirchneriella subcapitata. Mitig. Adapt. Strateg. Glob. Chang. 19, 1109-1117.
- Poulter, B., Frank, D., Ciais, P., Myneni, R.B., Andela, N., Bi, J., et al., 2014. Contribution of semiarid ecosystems to interannual variability of the global carbon cycle. Nature 509, 600.
- Pour, N., Webley, P.A., Cook, P.J., 2018. Potential for using municipal solid waste as a resource for bioenergy with carbon capture and storage (BECCS). Int. J. Greenhouse Gas Control 68, 1-15.
- Qafoku, N.P., 2015. Climate-change effects on soils: accelerated weathering, soil carbon, and elemental cycling. Adv. Agron. 131 (131), 111-172.
- Rau, G.H., 2011. CO2 mitigation via capture and chemical conversion in seawater. Environ. Sci. Technol. 45, 1088-1092.
- Rau, G.H., 2014. In: Freedman, B., et al. (Eds.), Enhancing the ocean's role in CO2 mitigation. Springer, Netherlands, Dordrecht, pp. 817-824.
- Rau, G.H., Caldeira, K., 1999. Enhanced carbonate dissolution: a means of sequestering waste CO2 as ocean bicarbonate. Energy Convers. Manag. 40, 1803-1813.
- Raupach, M.R., Marland, G., Ciais, P., Le Quere, C., Canadell, J.G., Klepper, G., et al., 2007. Global and regional drivers of accelerating CO2 emissions. Proc. Natl. Acad. Sci. U. S. A. 104, 10288-10293.
- Raupach, M.R., Davis, S.J., Peters, G.P., Andrew, R.M., Canadell, J.G., Ciais, P., et al., 2014. Sharing a quota on cumulative carbon emissions. Nat. Clim. Chang. 4, 873-879.
- Read, P., Lermit, J., 2005. Bio-energy with carbon storage (BECS): a sequential decision approach to the threat of abrupt climate change. Energy 30, 2654-2671.
- Renforth, P., Henderson, G., 2017. Assessing ocean alkalinity for carbon sequestration. Rev. Geophys. 55, 636-674
- Renforth, P., Kruger, T., 2013. Coupling mineral carbonation and ocean liming. Energy Fuel 27, 4199-4207.
- Renforth, P., Manning, D.A.C., 2011. Laboratory carbonation of artificial silicate gels enhanced by citrate: implications for engineered pedogenic carbonate formation. Int. J. Greenhouse Gas Control 5, 1578-1586.
- Renforth, P., Manning, D.A.C., Lopez-Capel, E., 2009. Carbonate precipitation in artificial soils as a sink for atmospheric carbon dioxide. Appl. Geochem. 24, 1757-1764.
- Renforth, P., Washbourne, C.L., Taylder, J., Manning, D.A.C., 2011. Silicate production and availability for mineral carbonation. Environ. Sci. Technol. 45, 2035-2041
- Renforth, P., Jenkins, B.G., Kruger, T., 2013. Engineering challenges of ocean liming. Energy 60, 442-452.
- Rhodes, J.S., 2007. Carbon Mitigation with Biomass: An Engineering, Economic and Policy Assessment of Opportunities and Implications. Department of Engineering and Public Policy. PhD thesis. Carnegie Mellon University.
- Rockstrom, J., Steffen, W., Noone, K., Persson, A., Chapin, F.S., Lambin, E.F., et al., 2009. A safe operating space for humanity. Nature 461, 472-475.
- Ryden, M., Lyngfelt, A., Langorgen, O., Larring, Y., Brink, A., Teir, S., et al., 2017. Negative CO2 emissions with chemical-looping combustion of biomass - a Nordic Energy Research flagship project. 13th International Conference on Greenhouse Gas Control Technologies. vol. 114, pp. 6074-6082 Ghgt-13.
- Sanchez, D.L., Nelson, J.H., Johnston, J., Mileva, A., Kammen, D.M., 2015. Biomass enables the transition to a carbon-negative power system across western North America. Nat. Clim. Chang. 5, 230-234.
- Sanz-Perez, E.S., Murdock, C.R., Didas, S.A., Jones, C.W., 2016. Direct capture of CO2 from ambient air. Chem. Rev. 116, 11840-11876.
- Schiebahn, S., Grube, T., Robinius, M., Tietze, V., Kumar, B., Stolten, D., 2015. Power to gas: technological overview, systems analysis and economic assessment for a case study in Germany. Int. J. Hydrog. Energy 40, 4285-4294.
- Schimel, D.S., House, J.I., Hibbard, K.A., Bousquet, P., Ciais, P., Peylin, P., et al., 2001. Recent patterns and mechanisms of carbon exchange by terrestrial ecosystems. Nature 414, 169-172.
- Schmidt, M.W.I., Torn, M.S., Abiven, S., Dittmar, T., Guggenberger, G., Janssens, I.A., et al., 2011. Persistence of soil organic matter as an ecosystem property. Nature 478, 49–56.
- Schmidt, H.P., Anca-Couce, A., Hagemann, N., Werner, C., Gerten, D., Lucht, W., et al., 2019. Pyrogenic carbon capture and storage. Glob. Change Biol. Bioenergy. 11, 573-591. Scott, C.E., Rap, A., Spracklen, D.V., Forster, P.M., Carslaw, K.S., Mann, G.W., et al., 2014. The
- direct and indirect radiative effects of biogenic secondary organic aerosol. Atmos. Chem. Phys. 14, 447-470.
- Scragg, A.H., Illman, A.M., Carden, A., Shales, S.W., 2002. Growth of microalgae with increased calorific values in a tubular bioreactor. Biomass Bioenergy 23, 67-73.
- Selosse, S., Ricci, O., 2014. Achieving negative emissions with BECCS (bioenergy with carbon capture and storage) in the power sector; new insights from the TIAM-FR (TIMES Integrated Assessment Model France) model, Energy 76, 967–975.
- Shekhah, O., Belmabkhout, Y., Chen, Z.J., Guillerm, V., Cairns, A., Adil, K., et al., 2014. Madeto-order metal-organic frameworks for trace carbon dioxide removal and air capture. Nat. Commun. 5.

- Shepherd, J., Caldiera, K., Cox, P., Haigh, J., Keith, D., Launder, B., et al., 2009, Geoengineering the Climate: Science, Governance and Uncertainty. The Royal Society, London.
- Singh, U.B., Ahluwalia, A.S., 2013. Microalgae: a promising tool for carbon sequestration. Mitig. Adapt. Strateg. Glob. Chang. 18, 73–95.
- Smith, P., 2016. Soil carbon sequestration and biochar as negative emission technologies. Glob. Chang. Biol. 22, 1315-1324.
- Smith, P., Davis, S.J., Creutzig, F., Fuss, S., Minx, J., Gabrielle, B., et al., 2016. Biophysical and economic limits to negative CO2 emissions. Nat. Clim. Chang. 6, 42-50.
- Smith, M.J., Walker, C.F., Bell, T.G., Harvey, M.J., Saltzman, E.S., Law, C.S., 2018. Gradient flux measurements of sea-air DMS transfer during the Surface Ocean Aerosol Production (SOAP) experiment, Atmos. Chem. Phys. 18, 5861-5877.
- Steffen, W., Crutzen, P.J., McNeill, J.R., 2007. The Anthropocene: are humans now overwhelming the great forces of nature. Ambio 36, 614-621.
- Stolaroff, J.K., 2006. Capturing CO2 from Ambient Air: A Feasibility Assessment. PhD The-
- sis. Carnegie Mellon University, Pittsburgh, PA. Stolaroff, J.K., Keith, D.W., Lowry, G.V., 2008. Carbon dioxide capture from atmospheric air using sodium hydroxide spray. Environ. Sci. Technol. 42, 2728–2735.
- Stuart, G.S., Stevens, R.G., Partanen, A.I., Jenkins, A.K.L., Korhonen, H., Forster, P.M., et al., 2013. Reduced efficacy of marine cloud brightening geoengineering due to inplume aerosol coagulation: parameterization and global implications. Atmos. Chem. Phys. 13, 10385-10396
- Swarnalatha, G.V., Hegde, N.S., Chauhan, V.S., Sarada, R., 2015. The effect of carbon dioxide rich environment on carbonic anhydrase activity, growth and metabolite production in indigenous freshwater microalgae. Algal Res. 9, 151-159.
- Tian, H.Q., Lu, C.Q., Ciais, P., Michalak, A.M., Canadell, J.G., Saikawa, E., et al., 2016. The terrestrial biosphere as a net source of greenhouse gases to the atmosphere. Nature 531, 225.
- Tokimatsu, K., Konishi, S., Ishihara, K., Tezuka, T., Yasuoka, R., Nishio, M., 2016. Role of innovative technologies under the global zero emissions scenarios. Appl. Energy 162, 1483-1493.
- Veselovskaya, J.V., Parunin, P.D., Okunev, A.G., 2017. Catalytic process for methane production from atmospheric carbon dioxide utilizing renewable energy. Catal. Today 298, 117-123,
- Vidyashankar, S., Deviprasad, K., Chauhan, V.S., Ravishankar, G.A., Sarada, R., 2013. Selection and evaluation of CO2 tolerant indigenous microalga Scenedesmus dimorphus for unsaturated fatty acid rich lipid production under different culture conditions. Bioresour. Technol. 144, 28-37.
- Vilches, T.B., Lind, F., Ryden, M., Thunman, H., 2017. Experience of more than 1000 h of operation with oxygen carriers and solid biomass at large scale. Appl. Energy 190, 1174-1183.
- van Vuuren, D.P., Stehfest, E., Gernaat, D.E.H.J., van den Berg, M., Bijl, D.L., de Boer, H.S., et al., 2018. Alternative pathways to the 1.5 degrees C target reduce the need for negative emission technologies. Nat. Clim. Chang. 8, 391 (-+)
- Walsh, B., Ciais, P., Janssens, I.A., Penuelas, J., Riahi, K., Rydzak, F., et al., 2017. Pathways for balancing CO2 emissions and sinks. Nat. Commun. 8.
- Wang, T., Liu, J., Lackner, K.S., Shi, X.Y., Fang, M.X., Luo, Z.Y., 2016. Characterization of kinetic limitations to atmospheric CO2 capture by solid sorbent. Greenhouse Gases Sci. Technol. 6, 138-149.
- Warren, R., Lowe, J.A., Arnell, N.W., Hope, C., Berry, P., Brown, S., et al., 2013. The AVOID programme's new simulations of the global benefits of stringent climate change mitigation. Clim. Chang. 120, 55-70.
- Washbourne, C.L., Renforth, P., Manning, D.A.C., 2012. Investigating carbonate formation in urban soils as a method for capture and storage of atmospheric carbon. Sci. Total Environ, 431, 166-175.
- Washbourne, C.L., Lopez-Capel, E., Renforth, P., Ascough, P.L., Manning, D.A.C., 2015. Rapid removal of atmospheric CO2 by urban soils. Environ. Sci. Technol. 49, 5434-5440.
- Watanabe, K., Kuwae, T., 2015. How organic carbon derived from multiple sources contributes to carbon sequestration processes in a shallow coastal system? Glob. Chang. Biol. 21, 2612-2623.
- Wei, X.R., Shao, M.G., Gale, W., Li, L.H., 2014. Global pattern of soil carbon losses due to the conversion of forests to agricultural land. Sci. Rep. 4.
- Whiteley, N.M., 2011. Physiological and ecological responses of crustaceans to ocean acidification. Mar. Ecol. Prog. Ser. 430, 257-271.
- Williamson, P., Wallace, D.W.R., Law, C.S., Boyd, P.W., Collos, Y., Croot, P., et al., 2012. Ocean fertilization for geoengineering: a review of effectiveness, environmental impacts and emerging governance. Process. Saf. Environ. Prot. 90, 475-488.
- Windeatt, J.H., Ross, A.B., Williams, P.T., Forster, P.M., Nahil, M.A., Singh, S., 2014. Characteristics of biochars from crop residues: potential for carbon sequestration and soil amendment. J. Environ. Manag. 146, 189-197.
- Workman, M., McGlashan, N., Chalmers, H., Shah, N., 2011. An assessment of options for CO2 removal from the atmosphere. 10th International Conference on Greenhouse Gas Control Technologies. vol. 4, pp. 2877-2884.
- Wurzbacher, J.A., Gebald, C., Steinfeld, A., 2011. Separation of CO2 from air by temperature-vacuum swing adsorption using diamine-functionalized silica gel. Energy Environ. Sci. 4, 3584-3592.
- Wurzbacher, J.A., Gebald, C., Brunner, S., Steinfeld, A., 2016. Heat and mass transfer of temperature-vacuum swing desorption for CO2 capture from air. Chem. Eng. J. 283, 1329-1338.
- Zeman, F., 2007. Energy and material balance of CO2 capture from ambient air. Environ. Sci. Technol. 41, 7558-7563.
- Zeman, F., 2008. Experimental results for capturing CO2 from the atmosphere (R&D note). AICHE I. 54, 1396-1399.
- Zhu, Z.C., Piao, S.L., Myneni, R.B., Huang, M.T., Zeng, Z.Z., Canadell, J.G., et al., 2016. Greening of the Earth and its drivers, Nat. Clim. Chang. 6 (791-+).